

INTERGRAIN Maxiproof Matt

PRODUCT CODE 552-97145

Data Sheet No. NZDD1063

APPROVALS

Description

INTERGRAIN Maxiproof Matt is an aliphatic interior/exterior moisture-cured polyurethane with added UV absorbers.

Features

 Aliphatic
 Moisture-cured
 Polyurethane resin
 U.V. Absorbers

Benefits

 Non-yellowing. Externally durable
 Performs over a wide temperature range
 Excellent abrasion resistance
 Minimises colour change of timber over time

Uses

Use INTERGRAIN Maxiproof on interior timber, parquetry or cork flooring (whether natural or coloured) and benchtops. It is also suitable for domestic interior concrete floors (foot traffic) and exterior masonry surfaces such as blockwork and tilt up panels.

Performance Guide

Weather Formulated for interior and exterior use

Heat Up to 120°C. Yellowing and embrittlement will occur if subjected to continuous heat.

Water Excellent resistance except to continuous immersion (ponding)


Solvent Resists splashes of most common solvents and cleaners

Abrasion Excellent abrasion and mar resistance

Typical Properties and Application Data

Gloss Level 10-15% at 60 degrees

Thinner Maxiproof Thinners

Gloss Level Ind

Spread Rate 8.0 sqm/L

Volume Solids 45.0

Components 1

Colour Clear

Number of Coats 3

Shelf life 12 months in unopened containers

V.O.C Level 708 g/L

Wet film per coat Recommended 125 µm

Touch Dry 4 Hours

Dry film per coat Recommended 41 µm

Clean Up Thoroughly clean all equipment with Maxiproof Thinners

Recoat 8 Hours

Application Method


INTERGRAIN Maxiproof Matt

Data Sheet No. NZDD1063

Application Guide

Surface Preparation

NEW TIMBER

All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants. Wash with mineral turpentine if needed to remove wax and grease, and allow to dry.

Surface should be sanded in accordance with the Abrasive manufacturers recommendations.

Remove all traces of dust from the work area.

Fill nail holes with a water-based wood putty - do not use a linseed oil putty

PREVIOUSLY COATED TIMBER

All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants.

Surface should be sanded in accordance with the Abrasive manufacturers recommendations.

Remove all traces of dust from the work area.

Application Procedure and Equipment

Stir thoroughly before and during use with a broad flat stirrer to maintain a uniform solution.

Apply by brush, pad or roller, always laying off along the grain.

Brush, applicator or short-nap roller

Health and Safety

MSDS Number 10819

Using Safety Precautions For detailed information refer to product label and the current Material Safety Data Sheet available through Dulux Woodcare Sales and Customer Service Office 0800 222 687.

Health Effects Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation and spray mists may produce respiratory irritation and headaches.
This product contains small traces of free-isocyanate monomer and should not be used by, or near, people who are sensitive to isocyanates, or, who have respiratory complaints

Flammability This product is flammable.

Protective Equipment Wear eye protection, protective clothing and gloves, and a respirator with a combined vapour/particulate cartridge. If spraying (not recommended) a positive air-feed mask must be used in accordance with A.S. 1715

Storage Store and use away from sources of heat and ignition.

Disposal Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.

In the case of emergency please call 0800 734 607

Data Sheet	INTERGRAIN Maxiproof Matt		
DuSpec Data Code	NZDD1063	Page No	2 of 3
Issue No	5.0	Date Issued	21/06/2010

INTERGRAIN Maxiproof Matt

Data Sheet No. NZDD1063

Precautions and Limitations

Do not apply product if temperature is below 10°C or above 30°C or is likely to reach these temperatures during the drying period. Equally, relative humidity should not exceed 85%.
Moisture content of timber should be close to equilibrium moisture content, usually 10-15%, but not exceeding 15%, for satisfactory application.
Product must be used within 4 weeks of opening container. Shelf life is 12 months in unopened container.

Transport and Storage

Pack A	552-97145		
Sizes	4 Litre	1 Litre	
Weight	4.8 Kg	1.2Kg	
Dangerous Goods Class	3b		
Shipment Name	PAINTS, flammable liquid, high flash point.		
		Flash point	47C
		UN Number	1263
		Package Group	III

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118

Data Sheet	INTERGRAIN Maxiproof Matt		
DuSpec Data Code	NZDD1063	Page No	3 of 3
Issue No	5.0	Date Issued	21/06/2010