

## INTERGRAIN Maxiproof Gloss

**PRODUCT CODE** 552-97143

**Data Sheet No.** NZDD1064

**APPROVALS**

### Description

INTERGRAIN Maxiproof Gloss is an aliphatic interior/exterior moisture-cured polyurethane with added UV absorbers.

### Features

 Aliphatic  
 Moisture-cured  
 Polyurethane resin  
 U.V. Absorbers

### Benefits

 Non-yellowing. Externally durable  
 Performs over a wide temperature range  
 Excellent abrasion resistance  
 Minimises colour change of timber over time

### Uses

Use INTERGRAIN Maxiproof on interior and exterior timber, parquetry, masonry, concrete or cork flooring (whether natural or coloured) and benchtops.

### Performance Guide

**Weather** Formulated for interior and exterior use

**Heat** Up to 120°C. Yellowing and embrittlement will occur if subjected to continuous heat.

**Water** Excellent resistance except to continuous immersion (ponding)


**Solvent** Resists splashes of most common solvents and cleaners

**Abrasion** Excellent abrasion and mar resistance

### Typical Properties and Application Data

**Gloss Level** 90-95% at 60 degrees

**Thinner** Maxiproof Thinners

**Gloss Level Ind**

**Spread Rate** 8.0 sqm/L

**Volume Solids** 45.0

**Components** 1

**Colour** Clear

**Number of Coats** 3

**Shelf life** 12 months in unopened containers

**V.O.C Level** 562 g/L

**Wet film per coat** Recommended 125 µm

**Touch Dry** 4 Hours

**Dry film per coat** Recommended 41 µm

**Clean Up** Thoroughly clean all equipment with Maxiproof Thinners

**Recoat** 8 Hours

**Application Method**


**INTERGRAIN Maxiproof Gloss**

Data Sheet No. NZDD1064

**Application Guide****Surface Preparation****NEW TIMBER**

All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants. Wash with mineral turpentine if needed to remove wax and grease, and allow to dry.

Surface should be sanded in accordance with the Abrasive manufacturers recommendations.

Remove all traces of dust from the work area.

Fill nail holes with a water-based wood putty - do not use a linseed oil putty

**PREVIOUSLY COATED TIMBER**

All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants.

Surface should be sanded in accordance with the Abrasive manufacturers recommendations.

Remove all traces of dust from the work area.

**Application Procedure and Equipment**

Stir thoroughly before and during use with a broad flat stirrer to maintain a uniform solution.

Apply by brush, pad or roller, always laying off along the grain.

Brush, applicator or short-nap roller

**Health and Safety**

**MSDS Number** 10817

**Using Safety Precautions** For detailed information refer to product label and the current Material Safety Data Sheet available through Dulux Woodcare Sales and Customer Service Office 0800 222 687.

**Health Effects** Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation and spray mists may produce respiratory irritation and headaches.  
This product contains small traces of free-isocyanate monomer and should not be used by, or near, people who are sensitive to isocyanates, or, who have respiratory complaints

**Flammability** This product is flammable.

**Protective Equipment** Wear eye protection, protective clothing and gloves, and a respirator with a combined vapour/particulate cartridge. If spraying (not recommended) a positive air-feed mask must be used in accordance with A.S. 1715

**Storage** Store and use away from sources of heat and ignition.

**Disposal** Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.

**In the case of emergency please call 0800 734 607**

<b>Data Sheet</b>	INTERGRAIN Maxiproof Gloss		
<b>DuSpec Data Code</b>	NZDD1064	<b>Page No</b>	2 of 3
<b>Issue No</b>	7.0	<b>Date Issued</b>	14/12/2011

**INTERGRAIN Maxiproof Gloss**

<b>Data Sheet No.</b>	<b>NZDD1064</b>
-----------------------	-----------------

**Precautions and Limitations**

Do not apply product if temperature is below 10°C or above 30°C or is likely to reach these temperatures during the drying period. Equally, relative humidity should not exceed 85%.  
 Moisture content of timber should be close to equilibrium moisture content, usually 10-15%, but not exceeding 15%, for satisfactory application.  
 Product must be used within 4 weeks of opening container. Shelf life is 12 months in unopened container.

**Transport and Storage**

<b>Pack A</b>	552-97143	<b>Flash point</b>	47C
<b>Sizes</b>	4 Litre	<b>UN Number</b>	1263
<b>Weight</b>	4.8 Kg	<b>Package Group</b>	III
<b>Dangerous Goods Class</b>	3b		
<b>Shipment Name</b>	PAINTS, flammable liquid, high flash point.		

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118

<b>Data Sheet</b>	INTERGRAIN Maxiproof Gloss		
<b>DuSpec Data Code</b>	NZDD1064	<b>Page No</b>	3 of 3
<b>Issue No</b>	7.0	<b>Date Issued</b>	14/12/2011