

Floorproof FloorProof Gloss

NZDW1024

Part A	552-97141
--------	-----------

Description

Floorproof Gloss is a one pack, aromatic, moisture cured polyurethane that dries to a tough, hard wearing clear gloss finish.

Features

- Moisture cured
- Polyurethane resin

Benefits

- Performs over a wide temperature range
- Excellent abrasion resistance




Uses

Floorproof Gloss is suitable for use on all interior timber, parquetry and cork flooring.

Performance Guide

Weather	For interior use only	Heat Resistance	Up to 120C. Yellowing and embrittlement will occur if subjected to continuous heat
Water	Excellent resistance except to continuous immersion or ponding.	Solvent	Resists splashes of most common solvents and cleaners
Abrasion	Excellent abrasion and mar resistance		

Typical Properties

Gloss Level	90-95 at 60 degrees	Colour	Clear																								
Components	1	Number Of Coats	3																								
Toxicity	Lead free. Dry film is non toxic.	V.O.C. Level	550 g /L																								
Shelf Life	12 months unopened	Sanding Properties	Good																								
Touch Dry	4 Hours																										
Clean Up	 Thinner																										
Clean Up Description	Clean all equipment using Intergrain Maxiproof Thinners																										
Application Method	  Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">45</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">125</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">41</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">8 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">8</td> </tr> </table>			Solids By Volume	45				Min	Max	Recommended	Wet Film Per Coat (microns)			125	Dry Film Per Coat (microns)			41	Recoat Time (min)	8 Hours	Indefinite		Theoretical Spread Rate (m ² /L)			8
Solids By Volume	45																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			125																								
Dry Film Per Coat (microns)			41																								
Recoat Time (min)	8 Hours	Indefinite																									
Theoretical Spread Rate (m ² /L)			8																								
Typical Properties Notes	Dry Floor Slip resistance as per AS/NZS 366.1: 1993 is 1.05.																										

Application Guide

Surface Preparation	<ul style="list-style-type: none"> NEW TIMBER All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other surface contaminants. All surfaces should be lightly sanded. Remove all traces of dust from the work area. Fill all nail holes with a suitable water based putty - Do not use Linseed Oil Putty. PREVIOUSLY COATED TIMBER All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other surface contaminants. All surfaces should be lightly sanded. Remove all traces of dust from the work area.
Application Procedure And Equipment	<ul style="list-style-type: none"> Apply with a brush, pad or roller always laying off in the grain direction. Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action. Do not shake or thin.

Health And Safety

MSDS Number	10821	Using Safety Precautions	For detailed information refer to product label and the current Material Safety Data Sheet available through Dulux Woodcare Sales and Customer Service Office 0800 222 687.
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-cds-020-000000010821.pdf		
Health Effects	Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation and spray mists may cause respiratory irritation and headaches. This product contains small traces of free isocyanate monomer and should not be used by or near people who are sensitive to isocyanates or who have respiratory complaints.	Flammability	This product is flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves and a respirator with a combined vapour particle cartridge. If spraying (not recommended) a positive air feed mask must be used in accordance to AS1715.	Storage	Store away from sources of heat and ignition.
Disposal	Do not contaminate stormwater with product or product washings. Do not pour unused paint down the drain. Dispose of product and recycle container in accordance to local authority regulations. Check with your regional council first.		

In the case of emergency, please call 0800 734 607

Precautions And Limitations

Do not apply product if air or substrate temperature is below 10C or above 30C or is likely to reach these temperatures during the drying period. Moisture content of timber should be close to equilibrium moisture content of around 10-15%, but not exceeding 15% for satisfactory application. For interior use only. Relative humidity should not exceed 85%.

Transport And Storage

Pack A	552-97141	Shipment Name	PAINTS, flammable liquid, high flash point
Size 4 Litre	Weight 4.8Kg		
Flash Point	47C	UN Number	1263
Dangerous Goods Class	3b	Package Group	III

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118