

**INTERGRAIN Floorproof Satin**

PRODUCT CODE 552-97142

Data Sheet No. NZDW1025

**APPROVALS**

**Description**

Intergrain Floorproof Satin is a one pack, aromatic, moisture cured polyurethane that dries to a tough, hard wearing clear satin finish.

**Features**

Moisture cured  
 Consistent satin finish  
 Polyurethane resin

**Benefits**

Performs over a wide temperature range  
 Natural subdued appearance on timber  
 Excellent abrasion resistance


**Uses**

Intergrain Floorproof Satin is suitable for use on all interior timber, parquetry and cork flooring.

**Performance Guide**

<b>Weather</b>	For interior use only	<b>Heat</b>	Up to 120C. Yellowing and embrittlement will occur if subjected to continuous heat
<b>Water</b>	Excellent resistance except to continuous immersion or ponding.	<b>Solvent</b>	Resists splashes of most common solvents and cleaners
<b>Abrasion</b>	Excellent abrasion and mar resistance		

**Typical Properties and Application Data**

<b>Gloss Level</b>	60-70 at 60 degrees	<b>Thinner</b>	Intergrain Maxiproof Thinners
<b>Gloss Level Ind</b>		<b>Spread Rate</b>	8.0 sqm/L
<b>Volume Solids</b>	45.0	<b>Components</b>	1
<b>Colour</b>	Clear	<b>Toxicity</b>	Lead free. Dry film is non toxic.
<b>Number of Coats</b>	3	<b>Shelf life</b>	12 months unopened
<b>V.O.C Level</b>	580g/L	<b>Sanding Properties</b>	Good
<b>Wet film per coat</b>	Recommended 125 µm	<b>Touch Dry</b>	4 Hours
<b>Dry film per coat</b>	Recommended 41 µm	<b>Clean Up</b>	Clean all equipment using Intergrain Maxiproof Thinners
<b>Recoat</b>	8 Hours		



**Application Method**



# INTERGRAIN Floorproof Satin

Data Sheet No. NZDW1025

## Application Guide

### Surface Preparation

#### NEW TIMBER

All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other surface contaminants. Surface should be lightly sanded in accordance with the abrasive manufacturers recommendations. Remove all traces of dust from the work area. Fill all nail holes with a suitable water based putty - Do not use Linseed Oil Putty.

#### PREVIOUSLY COATED TIMBER

All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other surface contaminants. Surface should be lightly sanded in accordance with the abrasive manufacturers recommendations. Remove all traces of dust from the work area.

### Application Procedure and Equipment

Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action. Do not shake or thin. Apply with a brush, pad or roller always laying off in the grain direction. Brush, applicator pad or short nap roller

## Health and Safety

**MSDS Number** 10820

**Using Safety Precautions** For detailed information refer to product label and the current Material Safety Data Sheet available through Dulux Woodcare Sales and Customer Service Office 0800 222 687.

**Health Effects** Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation and spray mists may cause respiratory irritation and headaches. This product contains small traces of free isocyanate monomer and should not be used by or near people who are sensitive to isocyanates or who have respiratory complaints.

**Flammability** This product is flammable.

**Protective Equipment** Wear eye protection, protective clothing and gloves and a respirator with a combined vapour particle cartridge. If spraying (not recommended) a positive air feed mask must be used in accordance to AS1715.

**Storage** Store away from sources of heat and ignition.

**Disposal** Do not contaminate stormwater with product or product washings. Do not pour unused paint down the drain. Dispose of product and recycle container in accordance to local authority regulations. Check with your regional council first.

**In the case of emergency please call 0800 734 607**

## Precautions and Limitations

Do not apply product if air or substrate temperature is below 10C or above 30C or is likely to reach these temperatures during the drying period. Moisture content of timber should be close to equilibrium moisture content of around 10-15%, but not exceeding 15% for satisfactory application. For interior use only. Relative humidity should not exceed 85%.

<b>Data Sheet</b>	INTERGRAIN Floorproof Satin		
<b>DuSpec Data Code</b>	NZDW1025	<b>Page No</b>	2 of 3
<b>Issue No</b>	3.0	<b>Date Issued</b>	21/06/2010

**INTERGRAIN Floorproof Satin**

<b>Data Sheet No.</b>	<b>NZDW1025</b>
-----------------------	-----------------

**Transport and Storage**

<b>Pack A</b>	552-97142		
<b>Sizes</b>	4 Litre	<b>Flash point</b>	47C
<b>Weight</b>	4.8Kg	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	3b	<b>Package Group</b>	III
<b>Shipment Name</b>	PAINTS, flammable liquid, high flash point		

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118

<b>Data Sheet</b>	INTERGRAIN Floorproof Satin		
<b>DuSpec Data Code</b>	NZDW1025	<b>Page No</b>	3 of 3
<b>Issue No</b>	3.0	<b>Date Issued</b>	21/06/2010